

## APCO PA Thinner

### Production Description

PA thinner is a medium evaporating solvent with great solvency. It is recommended as a thinner for spraying application where fast curing is desired.

### Areas of Application

Can be used as thinner for spray applications. It has good solvency for dissolving various resin systems.

### Technical Data

Appearance	Low viscosity, colourless clear liquid
Specific Gravity	0.86
Boiling Point	140 °C
Thinning Recommendations	Spray application: 5 to 10% is required, depending on product. Refer individual product data sheet for specific recommendations.
Packs available	1 litre, 4 litre, 20 litre, 60 litre & 200 litre

### Flammability & Transport

- Highly flammable, Dangerous Goods Class 3.2.
- Keep away from heat and flame, eliminate any source of ignition.
- Soak all used cloths and rags immediately in water to prevent self-ignition.
- Ensure container is upright with lid secure.
- Ensure the container is secured in the vehicle for transport.

### Safety & Precautions

Refer to SDS for detail instructions.

The technical information and suggestions for use and application are given in good faith. Since conditions of use are beyond the manufacturer's control, information contained herein is without warranty, implied or otherwise. The manufacturer does not assume any liability for any loss or injury resulting from the use of the product. Cooler temperature, higher film thickness and higher humidity conditions will require longer drying times

Omega Paints Pty Ltd., 13-27 Melbourne Road, Riverstone NSW 2765 Phone (02) 9832 0000 /  
info@omegapaints.com.au  
Reviewed Aug2019

## Australian Paint Company Pty Ltd

### SYDNEY

13-27 Melbourne Road, Riverstone NSW 2765  
P: (02) 9832 0000

### BRISBANE

444 Newman Road, Geebung QLD 4034  
P: (07) 3265 7890

E: [info@apcocoatings.com.au](mailto:info@apcocoatings.com.au)  
[www.apcocoatings.com.au](http://www.apcocoatings.com.au)